dp pumps





dph(s)i horizontal stainless steel multi-stage centrifugal pump

Efficient, reliable and for a wide range of applications

made in holland

Based on the hydraulic design of the successful vertical multistage centrifugal pumps DPV. 'Best in class' hydraulic efficiency and proven reliability. Specially developed for applications with limited installation height.



Applications

- Water treatment
- Pressure boosting systems
- Transportation of drinking water
- Transportation of cooling water
- Hot water applications
- Industry general


Reliable

- Cast stainless steel pump foot AISI 316 or AISI 304
- Wetted parts (impeller, stage casing, shroud) in stainless steel - AISI 316 or AISI 304

Flexible

- More than 10 seal combinations possible in accordance with EN12756 (Fixed, Easy access and Cartridge)
- 2 x 2 plugs on each side of the casing
- Discharge connection can be optionally placed on the left or right side of the pump or on top of the pump

22,5 m ³ /hour
136 mwk
PN25
-20°C to +140°C
Suction side G1¼ Discharge side G2



Motors

- 50 Hz / 60 Hz
- DPH(S)I 2, 4 and 6 available with 2-pole motor,
- DPH(S)I 10 and 15 with 2 or 4-pole motor
- 1 and 3 phases
- Standard IE3 (≥0.75 kW), optional IE4 or IE5
- Max 7.5 kW
- Also suitable for NEMA motor

Features

- Available in low-NPSH configuration for extra low NPSH values
- Drinking water certification (WRAS/ACS)
- Certification and test certificates are available upon request: among others, LR, BV, ABS, DNV GL 2.1; 2.2; 3.1 and 3.2



Developed and manufactured in Holland

In our modern, almost fully automated factory (16,000 m²) in the Netherlands we process stainless steel into high-quality components for our pumps. With our modular assembly system we can assemble these pump parts into custom made pumps and test them, all within a few hours.



Kalkovenweg 13 | Alphen aan den Rijn • P.O. Box 28 | 2400 AA Alphen aan den Rijn | Holland t. +31 172 48 83 88 • dp@dp-pumps.com • www.dp-pumps.com